



DSH-250



ACCESSORIES

	
250 Controller	250 Motor
	
250 Idle Pulley	250 Hangers
	
250 Power Cable	250 Belt Bracket
	
250 Cable holder	250 Floor Guide
	
250 Remote Control	250 Stopper
	
Belt	Microwave Sensor

TECHNICAL DATA

Door form: single door / double door
 Loading weight: $\leq 1 \times 250\text{kg} / \leq 2 \times 200\text{kg}$
 Clean opening width: 1000-2800mm/1800-3800mm
 Power supply: AC 110-220V $\pm 10\%$, 50/60Hz
 Power consumption: <100W
 Opening speed: 200-460mm/S (adjustable)
 Closing speed: 200-460mm/S (adjustable)
 Open time: 1-9S (adjustable)
 Closed force F: >100N
 Manual force: <100N
 Humidity range: -20 ~ +50°C

FEATURES

Intelligent control system, various parameters can be flexibly adjusted by manual or remote control according to the selected controller. Low-noise power unit, motor, worm gear and reducer integrated.

It adopts modern design, applies high-power brushless motor and new mechanical components that are trusted by the world. The hanging parts are made of imported high-strength nylon, and the load capacity of the unit reaches 2×200Kg.

The electric lock function is safe and reliable.

The control unit can be connected with building fire center, when fire, the door can be hold open or hold closed for safety.

It is suitable for all kinds of large-channel, industrial workshops, etc. It runs smoothly, is easy to install and easy to maintain.

SECTIONAL VIEW

