




ACCESSORIES

 DSW-100N Unit	 DSW-100/100N Pull Arm	 DSW-100/100N Push Arm
 DSW-100/100N Front cover	 DSW-100/100N Remote Control	

Note: The DSW-100/100N pull arm and push arm are selected according to the requirements.

TECHNICAL DATA

Door form: single door
 Carrying weight: $\leq 1 \times 100\text{kg}$
 Applicable door width: $\leq 1200\text{mm}$
 Power supply voltage: $\text{AC}220\text{V} \pm 10\%$, 50/60Hz
 Opening time: 3-7S/90° (adjustable)
 Open time: 1-30S (adjustable)
 Protection level: IP12D
 Product weight (unit): 6.5kg
 Unit size(DSW100N): 540X95X82mm
 Ambient temperature: $-20 \sim +55^{\circ}\text{C}$



FEATURES

The DSW100 drive unit operates with low noise, reliable performance and safe use, providing more convenience for living and working environments.


The DSW100N is a new upgraded transformer-less drive that offers a wider range of supply power voltages. Provides interfaces such as sensors, access control, and security sensor protection, and is equipped with interfaces for magnetic electric lock and backup battery too.

UPS power can be configured to meet security requirements. Both them can realize Interlocking function between door and door.


If touch obstacles or personnel in operation, the door will open in the opposite direction.

Applicable to office buildings, storefronts, banks, factories, restaurants, hotels, shopping centers, laboratories, hospitals and other places.

SECTIONAL VIEW



Pull arm type installation:suitable for door leaf inward open



Push arm type installation:suitable for door leaf outward open

