



DSL-200L



ACCESSORIES

	
200L Controller	200L Motor
	
200L Idle Pulley	200L Hangers
	
200L Power Cable	200L Belt Bracket
	
200L Cable holder	200L Floor Guide
	
200L Remote Control	200L Stopper
	
Belt	Microwave Sensor

TECHNICAL DATA

Door form: single door / double door
 Loading weight: $\leq 1 \times 150\text{kg} / \leq 2 \times 120\text{kg}$
 Clean opening width: 600-1800mm/1000-3000mm
 Power supply: 220V $\pm 10\%$, 50/60Hz
 Rated power: 65W
 Opening speed: 200-500mm/S (adjustable)
 Closing speed: 200-500mm/S (adjustable)
 Open time: 0-9S (adjustable)
 Manual force: $< 30\text{N} / < 40\text{N}$
 Temperature range: $-20 \sim +50^\circ\text{C}$
 Humidity range: $< \text{relative humidity } 85\%$

FEATURES

The microcomputer control unit has self-learning function, the drive unit runs smoothly, safely and reliably; the function is complete and can be adapted to individual needs.

When the power is off, the automatic door will hold open and win the escape time. The 200L has a motor lock and no additional electric lock is required.

The European-style structure, the driving device, the control unit and the mechanism are installed on the top groove of the guide rail, the slide rail space is larger, the larger pulley runs smoothly and quiet.

The automatic door does not close when the safety beam guarantor passes. When the emergency stop switch is pressed in an emergency, the door stops running immediately and the safety is fully guaranteed.

Suitable for office buildings, storefronts, banks, restaurants, hotels, shopping centers, laboratories, hospitals and other places.

SECTIONAL VIEW

